



HEATER400-SMART-400V [↗](#)

Dispositivo de calentamiento inductivo

HEATER smart

Información técnica



Variante de su producto actual

Series	SMART	Extended functionality
--------	-------	------------------------

Datos técnicos

U	400 V	Tensión de funcionamiento
f	50 – 60 Hz	Frecuencia
P	12 kVA	Consumo de energía
I	30 A	Valor actual
$\vartheta_{h \text{ max}}$	240 °C	Max. heating temperature
	0 – 99 min	Heating time
	Touch	Display
	2	Magnetic probe, quantity
$\approx m$	176 kg	Peso



Funciones

+	Temperature hold
+	Automatic demagnetization, <2A/cm
+	Swivel arm
+	Log function
+	Delta-T control
+	Temperature control
+	Time control
+	Temperature and time control
+	Temperature and speed control
+	Overheating protection
only in temp. and speed mode	Automatic power reduction
+	Device supports horizontal / lying heating of the workpiece
+	Device supports vertical / hanging heating of the workpiece
+	Device mobile

Medidas

	1.214 mm	Longitud del HEATER
	560 mm	Anchura del HEATER
	990 mm	Altura del HEATER
B	320 mm	Space between poles
C	305 mm	Pole length
D	80x100	Pole cross section (mm ²)



Pieza de trabajo a calentar

	115 mm	Min. inner diameter workpiece, vertical heating: with included yoke
	30 mm	Min. inner diameter workpiece, vertical heating: with optional yoke
	135 mm	Min. inner diameter workpiece, horizontal heating
ØA max	850 mm	Diámetro exterior máx. de la pieza:
	315 mm	Max. workpiece width, vertical heating
	300 mm	Max. workpiece width, horizontal heating
m b max	400 kg	Peso máx. de la pieza

Información adicional

	1	Yokes included, quantity
	80x80	Yokes included, cross section (mm ²)