



**AP-3000S-HN-SET** [↗](#)

Hydraulic pump, air-driven

BETEX Air-hydraulic foot pump, 700 bar,
in set with pressure gauge, T-piece, hose,
couplings and steel box

Información técnica

**Variante de su producto actual**

Series	AP	Air-hydraulic pump
Version	HN	For use with hydraulic nuts

Datos técnicos

P _{max}	700 bar	Presión máxima de funcionamiento
\dot{V}	195 cm ³ @ 700 bar	Flujo de aceite/minuto
V _{max}	3 l	Volumen del depósito de aceite
V _{eff}	2,5 l	Cantidad utilizable de aceite
P _{AIR}	7 – 10 bar	Presión requerida en el suministro de aire
	3/8" NPT	Hose connection pump body
	Quick coupling G ¹ / ₄	Coupling
	9,1 kg	Weight pump
	376 x 243 x 253	Dimensions steel case (mm)
≈m	14,3 kg	Peso



Medidas

A	247 mm
B	190 mm
C	114 mm
D	309 mm
E	160 mm
F	90 mm
J	289 mm

Información adicional

preferably in combination with hydraulic nuts HYDNUT

Use

Productos relacionados

HYDNUT..-E
HYDNUT..-E-INCH
HYDNUT..-HEAVY