



HXPM-150T-3-ARM [↗](#)

Mobile hydraulic heavy duty hook puller

BETEX HXPM, 3-arm self-centering, max. pull-off force 1470 kN, mobile

Información técnica

Variante de su producto actual

| Series | HXPM | With cart |
|--------|------|-----------|
|--------|------|-----------|

Datos técnicos

| | | |
|---------------------|--------------------|---|
| U | 400 V | Voltage |
| | Three-phase AC | Current type |
| f | 50 – 60 Hz | Power frequency |
| s _{cm max} | 330 mm | Max. working stroke main cylinder |
| p _{max} | 700 bar | Max. operating pressure |
| w _{min} | 300 mm | Grip width, min. |
| w _{max} | 1.650 mm | Grip width, max. |
| t _{max} | 1.175 mm | Grip depth, max. |
| F _p | 1.470 kN | Pulling force |
| | 830 – 1330 | Working height range [bottom – center axis cylinder] (mm) |
| | 2990 x 1030 x 1390 | Dimensions [LxWxH] (mm) |
| ≈m | 1.200 kg | Peso |



Información adicional

electrically operated hydraulic unit for main cylinder, height adjustment as well as opening and closing of the gripper arms, safety valve prevents overloading

Functional principle

2 swivel castors with brake function, 2 fixed castors

Castors

Remote control, 7 adapter pieces (total length 1125 mm), security blanket

Included in delivery