



Ver detalles del producto en Medias

11.11.2025, 14:47:19 WET

SCHAEFFLER



NSSS-1010 [↗](#)

Hydraulic cylinder, 700 bar

BETEX NSSS Standard cylinder, single-acting, spring return, 10T class

Información técnica



Variante de su producto actual

Series	NSSS	Standard cylinder
Version	10T	Capacity class 10

Datos técnicos

	10	Capacity class (tons)
s_p	255,5 mm	Stroke
F_a	111 kN	Advance force, max.
P_{max}	700 bar	Presión máxima de funcionamiento
V_{oil}	406 cm ³	Oil capacity
A	350 mm	Height, retracted
B	605,5 mm	Height, extended
D	57 mm	Diámetro exterior
E	45 mm	Cylinder bore diameter
F	38 mm	Plunger diameter
H	19 mm	Base to advance port
J	40 mm	Saddle diameter
K	6 mm	Saddle protrusion from plunger
O	1"-8 UN	Plunger female thread (UN)
P	19 mm	Plunger thread length
U	39 mm	Base mounting holes, bolt circle
V	5/16"-18 UNC	Base mounting holes, thread (UNC)
Z	13 mm	Base mounting holes, thread depth
W	2 1/4"-14 UN	Collar thread (UN)
X	30 mm	Collar thread, length
≈m	6,4 kg	Peso



Información adicional

Hard chrome plated and hardened piston,
Rolled inside of cylinder,
Sandblasted outside with black nitride coating,
Coupling with dust cap

Product specifics