


**EP-13D-230V**

Hydraulic pump, electric

BETEX EP-13, 700 bar, usable oil volume 2.4 l

## Información técnica



## Variante de su producto actual

Series	EP	Electric pump
Version	HC	For use with hydraulic cylinders

## Datos técnicos

P max	700 bar	Presión máxima de funcionamiento
$\dot{V}_{H0}$	4.000 cm <sup>3</sup>	Flow rate/minute, without load
$\dot{V}_{H350}$	330 cm <sup>3</sup>	Flow rate/minute @ 350 bar
$\dot{V}_{H700}$	280 cm <sup>3</sup>	Flow rate/minute @ 700 bar
V max	3 l	Volumen del depósito de aceite
V eff	2,4 l	Cantidad utilizable de aceite
	double-acting	Cylinder compatibility
	3 pos./4-way	Valve type
	Forward/hold/reverse	Valve function
U	230 V	Tensión de funcionamiento
f	50 – 60 Hz	Power frequency
I	5 A	Amperage
	single-phase	Motor type
P M	0,45 kW	Motor power
	≈ 80 dB	Noise level @ 700 bar
≈m	26,6 kg	Peso



### Medidas

---

A	511,5 mm
B	148,5 mm
C	295,5 mm
D	251 mm
E	406 mm
F	206,5 mm
G	149,4 mm
H	3/8" NPT
J	485 mm

### Información adicional

---

Motor thermally protected, remote control with 3 m cable, automatic overload valve (700 bar)

Product specifics