


**EP-13S-120V**

Hydraulic pump, electric

BETEX EP-13, 700 bar, usable oil volume 2.4 l

Información técnica



Variante de su producto actual

Series	EP	Electric pump
Version	HC	For use with hydraulic cylinders

Datos técnicos

P _{max}	700 bar	Presión máxima de funcionamiento
\dot{V}_{H0}	4.000 cm ³	Flow rate/minute, without load
\dot{V}_{H350}	330 cm ³	Flow rate/minute @ 350 bar
\dot{V}_{H700}	280 cm ³	Flow rate/minute @ 700 bar
V _{max}	3 l	Volumen del depósito de aceite
V _{eff}	2,4 l	Cantidad utilizable de aceite
	single-acting	Cylinder compatibility
	2 pos./2-way	Valve type
	Hold/reverse	Valve function
U	120 V	Tensión de funcionamiento
f	50 – 60 Hz	Power frequency
I	10 A	Amperage
	single-phase	Motor type
P _M	0,45 kW	Motor power
	≈ 80 dB	Noise level @ 700 bar
≈m	25,8 kg	Peso



Medidas

A	511,5 mm
B	148,5 mm
C	295,5 mm
D	251 mm
E	406 mm
F	206,5 mm
G	149,4 mm
H	3/8" NPT
J	485 mm

Información adicional

Motor thermally protected, remote control with 3 m cable, automatic overload valve (700 bar)

Product specifics