


**EP-18S-120V**

Hydraulic pump, electric

BETEX EP-18, 700 bar, usable oil volume 6 l

Información técnica



Variante de su producto actual

Series	EP	Electric pump
Version	HC	For use with hydraulic cylinders

Datos técnicos

P max	700 bar	Presión máxima de funcionamiento
\dot{V}_{H0}	4.000 cm ³	Flow rate/minute, without load
\dot{V}_{H350}	330 cm ³	Flow rate/minute @ 350 bar
\dot{V}_{H700}	280 cm ³	Flow rate/minute @ 700 bar
V max	8 l	Volumen del depósito de aceite
V eff	6 l	Cantidad utilizable de aceite
	single-acting	Cylinder compatibility
	2 pos./2-way	Valve type
	Hold/reverse	Valve function
U	120 V	Tensión de funcionamiento
f	50 – 60 Hz	Power frequency
I	10 A	Amperage
	single-phase	Motor type
P M	0,45 kW	Motor power
	≈ 80 dB	Noise level @ 700 bar
≈m	31,7 kg	Peso



Medidas

A	504 mm
B	141,5 mm
C	311,6 mm
D	251 mm
E	391,5 mm
F	311,6 mm
G	149,4 mm
H	3/8" NPT
J	543,5 mm

Información adicional

Motor thermally protected, remote control with 3 m cable, automatic overload valve (700 bar)

Product specifics