


**EP-211S-120V**

Hydraulic pump, electric

BETEX EP-211, 700 bar, usable oil volume 9.5 l

## Información técnica



## Variante de su producto actual

Series	EP	Electric pump
Version	HC	For use with hydraulic cylinders

## Datos técnicos

P max	700 bar	Presión máxima de funcionamiento
$\dot{V}_{H0}$	8.200 cm <sup>3</sup>	Flow rate/minute, without load
$\dot{V}_{H350}$	840 cm <sup>3</sup>	Flow rate/minute @ 350 bar
$\dot{V}_{H700}$	750 cm <sup>3</sup>	Flow rate/minute @ 700 bar
V max	11 l	Volumen del depósito de aceite
V eff	9,5 l	Cantidad utilizable de aceite
	single-acting	Cylinder compatibility
	2 pos./2-way	Valve type
	Hold/reverse	Valve function
U	120 V	Tensión de funcionamiento
f	50 – 60 Hz	Power frequency
I	23 A	Amperage
	single-phase	Motor type
P M	1,12 kW	Motor power
	≈ 80 dB	Noise level @ 700 bar
≈m	35,6 kg	Peso



### Medidas

---

A	559 mm
B	176 mm
C	515,5 mm
D	300 mm
E	391,5 mm
F	224,4 mm
G	180 mm
H	3/8" NPT
J	515,5 mm

### Información adicional

---

Motor thermally protected, remote control with 3 m cable, automatic overload valve (700 bar)

Product specifics