


**EP-211SS-120V**

Hydraulic pump, electric

BETEX EP-211, 700 bar, usable oil volume 9.5 l, with solenoid valve

Información técnica



Variante de su producto actual

Series	EP	Electric pump
Version	HC	For use with hydraulic cylinders

Datos técnicos

P max	700 bar	Presión máxima de funcionamiento
\dot{V}_{H0}	8.200 cm ³	Flow rate/minute, without load
\dot{V}_{H350}	840 cm ³	Flow rate/minute @ 350 bar
\dot{V}_{H700}	750 cm ³	Flow rate/minute @ 700 bar
V max	11 l	Volumen del depósito de aceite
V eff	9,5 l	Cantidad utilizable de aceite
	single-acting	Cylinder compatibility
	2 pos./2-way solenoid valve	Valve type
	Hold/reverse	Valve function
U	120 V	Tensión de funcionamiento
f	50 – 60 Hz	Power frequency
I	23 A	Amperage
	single-phase	Motor type
P M	1,12 kW	Motor power
	≈ 80 dB	Noise level @ 700 bar
≈m	36,1 kg	Peso



Medidas

A	559 mm
B	176 mm
C	515,5 mm
D	300 mm
E	391,5 mm
F	224,4 mm
G	180 mm
H	3/8" NPT
J	515,5 mm

Información adicional

Motor thermally protected, remote control with 3 m cable, automatic overload valve (700 bar)

Product specifics