



## HXPM-100T-2/3-ARM [↗](#)

Mobile hydraulic heavy duty hook puller

BETEX HXPM, 2/3-arm self-centering, max. pull-off force 980 kN, mobile

### Información técnica

#### Variante de su producto actual

Series	HXPM <a href="#">↗</a>	With cart
--------	------------------------	-----------

#### Datos técnicos

U	400 V	Voltage
	Three-phase AC	Current type
f	50 – 60 Hz	Power frequency
s cm max	270 mm	Max. working stroke main cylinder
P max	700 bar	Max. operating pressure
w min	300 mm	Grip width, min.
w max	1.500 mm	Grip width, max.
t max	1.220 mm	Grip depth, max.
F p	980 kN	Pulling force
	820 – 1320	Working height range [bottom – center axis cylinder] (mm)
	2790 x 1030 x 1410	Dimensions [LxWxH] (mm)
≈m	1.120 kg	Peso



### Información adicional

electrically operated hydraulic unit for main cylinder, height adjustment as well as opening and closing of the gripper arms, safety valve prevents overloading	Functional principle
two- or three-arm puller (convertible)	Usability
2 swivel castors with brake function, 2 fixed castors	Castors
Remote control, 7 adapter pieces (total length 1125 mm), security blanket	Included in delivery