



## TKLT45X4000-U-EWL-G4 [↗](#)

### Carril perfilado

Guideways for linear ball bearing unit and four-row linear recirculating ball guidance system, for screw mounting from below

## Información técnica



### Variante de su producto actual

|                 |       |
|-----------------|-------|
| Size code       | 45    |
| Longitud        | ~4000 |
| Guideway design | U     |
| Accuracy class  | G4    |

### Medidas principales y datos de rendimiento

|                  |          |                                  |
|------------------|----------|----------------------------------|
| h                | 38 mm    | Height                           |
| b                | 45 mm    | Width rail                       |
| l <sub>max</sub> | 3.885 mm | Max length single piece guideway |
| ≈m               | 46,62 kg | Peso                             |



### Medidas de montaje

|              |         |                           |
|--------------|---------|---------------------------|
| $h_1$        | 20,8 mm | Longitud                  |
| $G_1$        | M12     | Thread, DIN ISO 4762-12.9 |
| $G1 M_A$     | 140 Nm  | Par de apriete            |
| $j_L$        | 105 mm  | Increment                 |
| $a_{L \min}$ | 16 mm   | Distance                  |
| $a_{L \max}$ | 90 mm   | Distance                  |
| $a_{R \min}$ | 16 mm   |                           |
| $a_{R \max}$ | 90 mm   |                           |
| $t_7$        | 20 mm   | Longitud de rosca         |
| $K_1$        | M12     | Thread                    |
| $K1 M_A$     | 140 Nm  | Tightening torque         |

### Información adicional

|          |      |                    |
|----------|------|--------------------|
| VMKB_064 | TKLT | Nombre de material |
|----------|------|--------------------|