



## TOOL-RAILWAY-AGGREGATE-2 [↗](#)

Mobile hydraulic device

for mounting/dismounting of tapered or cylindrical roller bearing units in wheelset bearings of rail vehicles, standard version

### Información técnica



#### Variante de su producto actual

| Series | TRAG | TOOL-RAILWAY-AGGREGATE |
|--------|------|------------------------|
|--------|------|------------------------|

#### Datos técnicos

|                    |                  |   |
|--------------------|------------------|---|
| U                  | 400 V            | Voltage   |
|                    | Three-phase AC   | Current type  |
| f                  | 50 – 60 Hz       | Power frequency   |
| P                  | 1,1 kW           | Consumo de energía  |
| F <sub>c max</sub> | 692 kN           | Max. contact force cylinder                               |
| s <sub>c max</sub> | 230 mm           | Max. working stroke cylinder                              |
| P <sub>max</sub>   | 700 bar          | Max. operating pressure                                   |
|                    | 435 – 995        | Working height range [bottom – center axis cylinder] (mm) |
|                    | 1050 x 550 x 900 | Dimensions [LxWxH] (mm)                                   |
| m                  | 155 kg           | Peso  |

#### Funciones

|  |                      |
|--|----------------------|
| electrically driven hydraulic unit, double action hollow piston cylinder | Functional principle |
| hydraulic with foot pedal, manually operated lowering valve              | Height adjustment    |
| 4 swivel castors with brake function                                     | Castors              |



### Información adicional

---

Product is manufactured to order. Request with specification of the application case to customer service.

Availability

only in conjunction with bearing/ application-specific tool set TOOL-RAILWAY-AXLE... (not included in delivery, separate on request)

Usability