

**W20-H6-RROC**

Eje macizo

solid shafts, with axial and/or radial threaded holes

Información técnica



Variante de su producto actual

Size code	20	
Tolerance diameter	H6	
Material	CF53	Heat treatable steel (material no.:1.1213)
Recubrimiento	RROC	Special coating Corrotect, anti corrosion protection

Medidas principales y datos de rendimiento

d_{LW}	20 mm	Diameter Shaft
L_{max}	6.000 mm	Length total maximum
$\approx m$	2,47 kg/m	Peso

Medidas de montaje

$d_{LW Tol}$	h6	Diameter Shaft
$h6 Tol$	0 μm	Diameter Shaft high
$h6 Tol$	-13 μm	Diameter Shaft low
SHD min	0,9 mm	Surface Hardness Depth
t_1	6 μm	Roundness
t_2	9 μm	Parallelism



Medidas principales

G 2	M6/M8/M10	Axial thread (size)
G 7	M5/M6	Radial thread (size)
B 01	M6/M8/M10	Drilling pattern axial thread one side
B 02	M6/M8/M10	Drilling pattern axial thread both side
B 03	M5/M6	Drilling pattern radial thread
B 04	M5/M6 + M6/M8/ M10	Drilling pattern radial thread+axial thread one side
B 05	M5/M6 + M6/M8/ M10	Drilling pattern radial thread+axial thread both side