

IMAGE  
COMING SOON**LFS86-C**

## Carril-guía

hollow section profile, with two raceway shafts; corrosion-resistant design possible

## Información técnica

## Variante de su producto actual




Size code	86	
Ejecución	C	Hollow section profile

## Medidas principales y datos de rendimiento

h	34 mm	Height
b	86 mm	Width
l <sub>max</sub>	6.000 mm	Length maximum
I <sub>y</sub>	613.720 mm <sup>4</sup>	Second moment of area
I <sub>z</sub>	155.160 mm <sup>4</sup>	Second moment of area
LF <sub>Q</sub>	1.185 mm <sup>2</sup>	Cross-sectional area
W <sub>y</sub>	16.587 mm <sup>3</sup>	Wider resistance torque
W <sub>z</sub>	8.866 mm <sup>3</sup>	Wider resistance torque

## Medidas de montaje

N <sub>1</sub>	13 mm	Bore diameter
N <sub>3</sub>	21 mm	Bore diameter





### Medidas

a <sub>2</sub>	76 mm	Distance
a <sub>L max</sub>	235 mm	Distance
a <sub>L min</sub>	17 mm	Distance
a <sub>R max</sub>	235 mm	
a <sub>R min</sub>	17 mm	
b <sub>1</sub>	71 mm	Anchura
d <sub>LW</sub>	10 mm	Diameter
e <sub>Z</sub>	17,5 mm	Distance
h <sub>1</sub>	21 mm	Height
h <sub>4</sub>	25,1 mm	Height
j <sub>L</sub>	250 mm	Increment