
**EGS20260-E40-S3E** [↗](#)

Tira

Strip, maintenance-free, material in accordance with ISO 3547-4, with steel backing

## Información técnica

**Variante de su producto actual**

Maintenance	Maintenance free
-------------	------------------

**Medidas principales y datos de rendimiento**

s <sub>3</sub>	2,005 mm	Wall thickness
B	260 mm	Width
B <sub>1</sub>	243 mm	Minimum usable width
L	500 mm	Strip length
≈m	1,966 kg	Peso

**Medidas**

s <sub>3min</sub>	-0,05 mm	Wall thickness lower tolerance
s <sub>3max</sub>	0 mm	Wall thickness upper tolerance
B <sub>min</sub>	-2 mm	Width , lower tolerance
B <sub>max</sub>	2 mm	Width, upper tolerance
L <sub>min</sub>	0 mm	Total length lower tolerance
L <sub>max</sub>	3 mm	Total width upper tolerance

**Rango de temperatura**

T <sub>min</sub>	-200 °C	Temperatura mín. de funcionamiento
T <sub>max</sub>	280 °C	Temperatura máx. de funcionamiento



### Características

---



Carga radial



Lubricación de por vida, ausencia de mantenimiento



No obturado



Espacio constructivo reducido