



IMAGE
COMING SOON

FAG

SPA2222-H-W-T-BL-D [↗](#)

Soporte tensor

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----------------|--------|------------------|
| d | 100 mm | Shaft diameter |
| d _c | 108 mm | Chamfer diameter |
| h | 270 mm | Height |
| a | 380 mm | Length total |

**Medidas**

| | | |
|-----|----------|---------------------------------|
| a 1 | 265 mm | Length guidance groove |
| a 2 | 135 mm | Distance shaft axis |
| g 1 | 149,2 mm | Total width with lid |
| g 2 | 177,2 mm | Width total shaft |
| m | 200 mm | Distance fork bore shaft center |
| r 1 | 45 mm | Fork radius |
| x | 70 mm | Fork clearance |
| x 1 | 70 mm | Fork flange diameter |
| u | 40 mm | Fork boring diameter |
| p | 40 mm | Inner fork width |
| p 1 | 76 mm | Outer fork width |
| f | 240 mm | Distance guidance grooves |
| f 1 | 53 mm | Width guidance groove |
| D | 200 mm | Outside diameter bearing |
| k | 2,5 mm | Axial displacement |
| g | 73 mm | Anchura del cuerpo de soporte |
| g 3 | 82,6 mm | Locking collar width |
| g 4 | 60,6 mm | Distance bearing center cover |
| t | 230 mm | Pitch circle diameter holes |
| s 2 | M12 | Agujero de fijación roscado |
| s 2 | 6 | Number of screwing holes |

Información adicional

| | |
|-----------|-----------------------|
| 22222..-K | Referencia rodamiento |
| H322 | Manguito de fijación |

