



IMAGE
COMING SOON

FAG

SPA2228-H-W-T-AF-D [↗](#)

Soporte tensor

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----------------|--------|------------------|
| d | 125 mm | Shaft diameter |
| d _c | 137 mm | Chamfer diameter |
| h | 330 mm | Height |
| a | 445 mm | Length total |

**Medidas**

| | | |
|-----|--------|---------------------------------|
| a 1 | 320 mm | Length guidance groove |
| a 2 | 160 mm | Distance shaft axis |
| g 1 | 166 mm | Total width with lid |
| g 2 | 196 mm | Width total shaft |
| m | 230 mm | Distance fork bore shaft center |
| r 1 | 55 mm | Fork radius |
| x | 70 mm | Fork clearance |
| x 1 | 70 mm | Fork flange diameter |
| u | 40 mm | Fork boring diameter |
| p | 40 mm | Inner fork width |
| p 1 | 76 mm | Outer fork width |
| f | 300 mm | Distance guidance grooves |
| f 1 | 53 mm | Width guidance groove |
| D | 250 mm | Outside diameter bearing |
| k | 3 mm | Axial displacement |
| g | 88 mm | Anchura del cuerpo de soporte |
| g 3 | 88 mm | Locking collar width |
| g 4 | 70 mm | Distance bearing center cover |
| t | 285 mm | Pitch circle diameter holes |
| s 2 | M16 | Agujero de fijación roscado |
| s 2 | 6 | Number of screwing holes |

Información adicional

| | |
|-----------|-----------------------|
| 22228..-K | Referencia rodamiento |
| H3128 | Manguito de fijación |