



IMAGE
COMING SOON

FAG

SPA2220-H-W-T-AL-D [↗](#)

Soporte tensor

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----------------|----------|------------------|
| d | 90 mm | Shaft diameter |
| d _c | 98 mm | Chamfer diameter |
| h | 250 mm | Height |
| a | 342,5 mm | Length total |

**Medidas**

| | | |
|------------------------------|-----------|---------------------------------|
| a 1 | 235 mm | Length guidance groove |
| a 2 | 117,5 mm | Distance shaft axis |
| g 1 | 141 mm | Total width with lid |
| g 2 | 168 mm | Width total shaft |
| m | 185 mm | Distance fork bore shaft center |
| r 1 | 40 mm | Fork radius |
| x | 67,5 mm | Fork clearance |
| x 1 | 65 mm | Fork flange diameter |
| u | 35 mm | Fork boring diameter |
| p | 36 mm | Inner fork width |
| p 1 | 70 mm | Outer fork width |
| f | 220 mm | Distance guidance grooves |
| f 1 | 40 mm | Width guidance groove |
| D | 180 mm | Outside diameter bearing |
| k | 2,5 mm | Axial displacement |
| g | 65 mm | Anchura del cuerpo de soporte |
| g 3 | 78 mm | Locking collar width |
| g 4 | 57 mm | Distance bearing center cover |
| t | 205 mm | Pitch circle diameter holes |
| s 2 | M8 | Agujero de fijación roscado |
| s 2 | 6 | Number of screwing holes |
| Información adicional | | |
| | 22220..-K | Referencia rodamiento |
| | H320 | Manguito de fijación |

