



IMAGE  
COMING SOON

**FAG**

**SPA3132-H-W-Y-BL-D** [↗](#)

Soporte tensor

## Información técnica



### Medidas principales y datos de rendimiento

|                |        |                  |
|----------------|--------|------------------|
| d              | 140 mm | Shaft diameter   |
| d <sub>c</sub> | 152 mm | Chamfer diameter |
| h              | 370 mm | Height           |
| a              | 625 mm | Length total     |

**Medidas**

|     |        |                                 |
|-----|--------|---------------------------------|
| a 1 | 370 mm | Length guidance groove          |
| a 2 | 185 mm | Distance shaft axis             |
| g 1 | 216 mm | Total width with lid            |
| g 2 | 229 mm | Width total shaft               |
| m   | 350 mm | Distance fork bore shaft center |
| r 1 | 90 mm  | Fork radius                     |
| x   | 160 mm | Fork clearance                  |
| x 1 | 100 mm | Fork flange diameter            |
| u   | 60 mm  | Fork boring diameter            |
| p   | 62 mm  | Inner fork width                |
| p 1 | 132 mm | Outer fork width                |
| f   | 340 mm | Distance guidance grooves       |
| f 1 | 75 mm  | Width guidance groove           |
| D   | 270 mm | Outside diameter bearing        |
| k   | 3 mm   | Axial displacement              |
| g   | 116 mm | Anchura del cuerpo de soporte   |
| g 3 | 108 mm | Locking collar width            |
| g 4 | 100 mm | Distance bearing center cover   |
| t   | 300 mm | Pitch circle diameter holes     |
| s 2 | M12    | Agujero de fijación roscado     |
| s 2 | 8      | Number of screwing holes        |

**Información adicional**

|            |                       |
|------------|-----------------------|
| 23132..-K  | Referencia rodamiento |
| H3132(-HG) | Manguito de fijación  |

