



IMAGE
COMING SOON

FAG

SPA3152-H-W-Y-BL-D [↗](#)

Soporte tensor

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----------------|--------|------------------|
| d | 240 mm | Shaft diameter |
| d _c | 256 mm | Chamfer diameter |
| h | 570 mm | Height |
| a | 990 mm | Length total |

**Medidas**

| | | |
|-----|----------|---------------------------------|
| a 1 | 550 mm | Length guidance groove |
| a 2 | 275 mm | Distance shaft axis |
| g 1 | 291 mm | Total width with lid |
| g 2 | 336 mm | Width total shaft |
| m | 565 mm | Distance fork bore shaft center |
| r 1 | 150 mm | Fork radius |
| x | 270 mm | Fork clearance |
| x 1 | 160 mm | Fork flange diameter |
| u | 100 mm | Fork boring diameter |
| p | 135 mm | Inner fork width |
| p 1 | 225 mm | Outer fork width |
| f | 540 mm | Distance guidance grooves |
| f 1 | 80 mm | Width guidance groove |
| D | 440 mm | Outside diameter bearing |
| k | 4 mm | Axial displacement |
| g | 175 mm | Anchura del cuerpo de soporte |
| g 3 | 150,5 mm | Locking collar width |
| g 4 | 132 mm | Distance bearing center cover |
| t | 490 mm | Pitch circle diameter holes |
| s 2 | M20 | Agujero de fijación roscado |
| s 2 | 8 | Number of screwing holes |

Información adicional

| | |
|-------------|-----------------------|
| 23152..-K | Referencia rodamiento |
| H3152X(-HG) | Manguito de fijación |