



FAG

S2BCH-220MM-FL [↗](#)

Soporte de apoyo

FAG split cylindrical roller bearing housing

Información técnica



Medidas principales y datos de rendimiento

d	220 mm	Diámetro del eje
H	≈ 641,35 mm	Housing height
B	≈ 749,3 mm	Length base
≈m	366,049 kg	Peso



Medidas

	S2BCH-220MM-FL	Complete unit float
	S2BCH-220MM-HD	Complete unit held
	PH-25	Housing designation
A	≈ 323,85 mm	Center height
C	≈ 279,4 mm	Base width
D	≈ 50,8 mm	Base height
E _{min}	≈ 530,225 mm	Base hole distance 1 min
E _{min}	≈ 568,325 mm	Base hole distance 1 max
F	≈ 190,5 mm	Base hole distance 2
s	4	# of mounting bolts
s	≈ 38,1 mm	Mounting bolt diameter
	S2BC-220MM-FL	Cartridge float bearing
	S2BC-220MM-HD	Cartridge held bearing
	S2C-900	Cartridge
G	≈ 274,637 mm	Length through bore
L	≈ 457,2 mm	Outside diameter cartridge
	≈ 3,629 kg	Grease capacity
	≈ 165,062 kg	Cartridge weight
	S2B-220MM-FL	Bearing float
	S2B-220MM-HD	Bearing held
	≈ 67,132 kg	Bearing weight
	900 Grp	Bearing group
C _r	≈ 964.490,976 N	Capacidad de carga dinámica, radial
C _{0r}	≈ 1.653.263,776 N	Capacidad de carga estática, radial
C _a	≈ 58.050,848 N	Capacidad de carga dinámica, axial
	1.091 1/min	Limiting speed
D ₀	≈ 393,7 mm	Outside diameter bearing
C ₀	≈ 162,611 mm	Width inner ring
B ₀	≈ 90,5 mm	Width outer ring





Ver detalles del producto en Medias

13.11.2025, 06:56:52 UTC

SCHAEFFLER

