



IMAGE
COMING SOON

FAG

SPA3034-H-W-Y-BL-D [↗](#)

Soporte tensor

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----------------|----------|------------------|
| d | 150 mm | Shaft diameter |
| d _c | 166 mm | Chamfer diameter |
| h | 360 mm | Height |
| a | 492,5 mm | Length total |

**Medidas**

| | | |
|-----|----------|---------------------------------|
| a 1 | 325 mm | Length guidance groove |
| a 2 | 162,5 mm | Distance shaft axis |
| g 1 | 178 mm | Total width with lid |
| g 2 | 203 mm | Width total shaft |
| m | 260 mm | Distance fork bore shaft center |
| r 1 | 70 mm | Fork radius |
| x | 90 mm | Fork clearance |
| x 1 | 90 mm | Fork flange diameter |
| u | 50 mm | Fork boring diameter |
| p | 60 mm | Inner fork width |
| p 1 | 150 mm | Outer fork width |
| f | 330 mm | Distance guidance grooves |
| f 1 | 65 mm | Width guidance groove |
| D | 260 mm | Outside diameter bearing |
| k | 2 mm | Axial displacement |
| g | 102 mm | Anchura del cuerpo de soporte |
| g 3 | 89 mm | Locking collar width |
| g 4 | 81 mm | Distance bearing center cover |
| t | 285 mm | Pitch circle diameter holes |
| s 2 | M12 | Agujero de fijación roscado |
| s 2 | 8 | Number of screwing holes |

Información adicional

| | |
|------------|-----------------------|
| 23034..-K | Referencia rodamiento |
| H3034(-HG) | Manguito de fijación |