



IMAGE
COMING SOON

FAG

SPA3268-H-W-Y-BL-D [↗](#)

Soporte tensor

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----------------|----------|------------------|
| d | 320 mm | Shaft diameter |
| d _c | 344 mm | Chamfer diameter |
| h | 740 mm | Height |
| a | 1.335 mm | Length total |

**Medidas**

| | | |
|-----|--------|---------------------------------|
| a 1 | 735 mm | Length guidance groove |
| a 2 | 385 mm | Distance shaft axis |
| g 1 | 434 mm | Total width with lid |
| g 2 | 489 mm | Width total shaft |
| m | 750 mm | Distance fork bore shaft center |
| r 1 | 200 mm | Fork radius |
| x | 310 mm | Fork clearance |
| x 1 | 170 mm | Fork flange diameter |
| u | 110 mm | Fork boring diameter |
| p | 213 mm | Inner fork width |
| p 1 | 300 mm | Outer fork width |
| f | 700 mm | Distance guidance grooves |
| f 1 | 123 mm | Width guidance groove |
| D | 620 mm | Outside diameter bearing |
| k | 5 mm | Axial displacement |
| g | 260 mm | Anchura del cuerpo de soporte |
| g 3 | 217 mm | Locking collar width |
| g 4 | 205 mm | Distance bearing center cover |
| t | 680 mm | Pitch circle diameter holes |
| s 2 | M30 | Agujero de fijación roscado |
| s 2 | 8 | Number of screwing holes |

Información adicional

| | |
|-----------|-----------------------|
| 23268..-K | Referencia rodamiento |
| H3268-HG | Manguito de fijación |

