



IMAGE
COMING SOON

FAG

SPA3148-H-W-Y-BF-D [↗](#)

Soporte tensor

Información técnica



Medidas principales y datos de rendimiento

| | | |
|----------------|--------|------------------|
| d | 220 mm | Shaft diameter |
| d _c | 236 mm | Chamfer diameter |
| h | 540 mm | Height |
| a | 925 mm | Length total |



Medidas

| | | |
|-----|--------|---------------------------------|
| a 1 | 520 mm | Length guidance groove |
| a 2 | 260 mm | Distance shaft axis |
| g 1 | 276 mm | Total width with lid |
| g 2 | 326 mm | Width total shaft |
| m | 515 mm | Distance fork bore shaft center |
| r 1 | 150 mm | Fork radius |
| x | 250 mm | Fork clearance |
| x 1 | 160 mm | Fork flange diameter |
| u | 100 mm | Fork boring diameter |
| p | 123 mm | Inner fork width |
| p 1 | 215 mm | Outer fork width |
| f | 500 mm | Distance guidance grooves |
| f 1 | 65 mm | Width guidance groove |
| D | 400 mm | Outside diameter bearing |
| k | 4 mm | Axial displacement |
| g | 152 mm | Anchura del cuerpo de soporte |
| g 3 | 148 mm | Locking collar width |
| g 4 | 122 mm | Distance bearing center cover |
| t | 455 mm | Pitch circle diameter holes |
| s 2 | M20 | Agujero de fijación roscado |
| s 2 | 8 | Number of screwing holes |

Información adicional

| | |
|-------------|-----------------------|
| 23148.-K | Referencia rodamiento |
| H3148X(-HG) | Manguito de fijación |

