



IMAGE  
COMING SOON

**FAG**

**SPA3052-H-W-Y-AF-D** [↗](#)

Soporte tensor

## Información técnica



### Medidas principales y datos de rendimiento

|                |        |                  |
|----------------|--------|------------------|
| d              | 240 mm | Shaft diameter   |
| d <sub>c</sub> | 256 mm | Chamfer diameter |
| h              | 540 mm | Height           |
| a              | 910 mm | Length total     |

**Medidas**

|     |        |                                 |
|-----|--------|---------------------------------|
| a 1 | 500 mm | Length guidance groove          |
| a 2 | 245 mm | Distance shaft axis             |
| g 1 | 226 mm | Total width with lid            |
| g 2 | 261 mm | Width total shaft               |
| m   | 515 mm | Distance fork bore shaft center |
| r 1 | 150 mm | Fork radius                     |
| x   | 250 mm | Fork clearance                  |
| x 1 | 140 mm | Fork flange diameter            |
| u   | 100 mm | Fork boring diameter            |
| p   | 123 mm | Inner fork width                |
| p 1 | 215 mm | Outer fork width                |
| f   | 500 mm | Distance guidance grooves       |
| f 1 | 65 mm  | Width guidance groove           |
| D   | 400 mm | Outside diameter bearing        |
| k   | 4 mm   | Axial displacement              |
| g   | 130 mm | Anchura del cuerpo de soporte   |
| g 3 | 113 mm | Locking collar width            |
| g 4 | 103 mm | Distance bearing center cover   |
| t   | 440 mm | Pitch circle diameter holes     |
| s 2 | M16    | Agujero de fijación roscado     |
| s 2 | 8      | Number of screwing holes        |

**Información adicional**

|             |                       |
|-------------|-----------------------|
| 23052..-K   | Referencia rodamiento |
| H3052X(-HG) | Manguito de fijación  |

